



Technical Data Sheet

Voller Tarmac Drivecoat Paint

Product Description

Voller Tarmac Drivecoat Paint can revive and seal tarmac, it is guaranteed to give your tarmac driveway a new lease of life. The paint can revitalise the appearance of your driveway and provide a powerful and durable coating across your whole tarmac surface. Our DIY friendly formula is a one pack application and is incredibly easy to apply.

Key Features

- Easy to use
- Resistant to Staining or Discolouring
- Excellent Coverage
- Touch Dry in under 3 hours
- Pet and Wildlife Friendly

Fields of Application

Tarmac, Asphalt, and similar Surfaces

Preparation

Ensure a thorough cleaning of the surface which is to be coated in Voller Tarmac Drivecoat Paint. Remove any loose or colour. Apply a minimum of 2 coats and re-coat after 4-6 hours when the surface has become touch dry.

Previously Painted Surfaces

Remove loose and flaking paint and apply as you would a bare surfacer

Application Methods

Brush

This Product can be applied by brush

flaking material from the surface and do so by wiping with a wire brush and vacuum if applicable. Clean the surface of any residue, dust, oil or grease using an appropriate cleaning solution and water and then allow to dry completely before attempting to paint. Damaged or cracked surfaces should be made good using mortar or other proprietary repair products before coating. **Please note:** that Tarmac and Asphalt are notoriously porous and as such the quality and porosity of the surface will impact the advertised coverage rates. Permeable asphalts may allow excess product to drain through, please apply in thin coats for best coverage.

Bare Surfaces

Stir thoroughly before use. Apply by brush, roller or pad in an even, cross rolled fashion. If using multiple tins intermix into a scuttle to ensure an even

Roller

This product can be applied by roller

Spray

This product can be applied via spraying.

Conventional Spray: Satisfactory through most equipment.

Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm² (2000 lb/in²) with a spray tip size of 0.38mm to 0.46mm (15 - 18thou) spray tip angle 65°. Filter mesh 60

Technical Specifications

Colour Range

Black

Dry Film Appearance

Semi Gloss

Spreading Rate

6-8m² /65-86ft² per coat per litre

Drying Times

Touch Dry 20°C

3 Hours

Recoating Time 20°C

2-6 Hours

Compositions

Voller Tarmac Drivecoat Paint is a water based acrylic coating

Appearance

Liquid

VOC Content

.Low-Medium

Odour

Low, inoffensive

Flammable

Not Flammable

Thinner

Water

Cleaning up

Clean up with soap and water. After cleaning up be sure to flush spray equipment with solvent to prevent rusting following manufacturer's instructions. Dispose of can in accordance with local authority guidelines.

Important Notes

Precautions

Keep out of reach of children. Ensure good ventilation during application and drying. If the product comes in contact with the eyes rinse immediately with plenty of water. To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. Contains no added lead.

Always pre test on a small area first to confirm colour acceptability

Use product only as directed

Do not apply in temperatures below 7°C

Do not apply at relative humidity levels of above 80% or within 3° of the dew point

Do not expose to chemicals or wash surface until 7 days after application

Storage

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Carefully reseal partly used containers. Do not store near foodstuffs. Protect from frost. To avoid risk of spillage, always store and transport in a secure and upright position.

Supply

Obtainable online or through retailers

Sizes

Available in 5l and 20l

Disposal

Some local authorities have special facilities for disposal of waste coatings.

Do not empty product into drains or watercourses.

Liability

Whilst these specifications are based on expert technical knowledge

and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should followed.

Information

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

Data Sheets

Data sheets on other Voller Products are available on request from our Technical Services Department.

Contact

Polycolor Industrial Coatings
92 Orchard Road
Strabane
Tyrone
BT82 9QU

Tel:

+

44 (028) 81658976 (Technical Services)

Email;

polycolorindustrialcoatings@gmail.com

Voller is a registered trademark of the Polycolor Industrial Coatings LTD